



DRILLMEC HYDRAULIC TOP DRIVE MODEL HTD250 Compact	
<p>Hydraulic top drive HTD250 Compact, with HPU diesel driven, suitable to operate at ambient temperature from -20°C to +50°C.</p>	
HYDRAULIC POWER UNIT	<p>Made by DRILLMEC. Hydraulic power unit will be mounted on a heavy-duty oilfield skid, inside a container, it driven by diesel engine (Caterpillar C15 540HP), it will supply power for: top drive head, back-up wrench, hydraulic jacks and outlet for Power tong.</p>
HYDRAULIC TOP DRIVE	<p>Made by DRILLMEC.</p> <ul style="list-style-type: none"> – I.D. full opening 2.9/16" (65 mm) – Variable speed 0 to 200 rpm – Torque range 0 to 390 daNm (28764 lbs-ft) – Max. pull up static 500,000 lbs – Max pressure Wash pipe suitable 5,000 psi – Connection Lower pin suitable 5" DP (NC50)
CONTROL PANEL & ADDITIONAL COMPONENTS	<p>Made by DRILLMEC.</p> <ul style="list-style-type: none"> – Saver sub – Handling skid – top drive – Top drive guide – Hoses top drive – Travelling block connection – Circulation swivel – Elevator links system (250 ton capacity) – Pipe handler – I-bop valve

